


## Planar Design Considerations

Designing a quality high-frequency power supply using planar transformers involves multiple considerations.

## Planar Design Considerations:

*Designing a high-quality, high-frequency power supply using planar transformers requires careful consideration of several critical factors:*

- 1. Switching Frequency:** Higher switching frequencies reduce transformer size but increase losses due to intensified skin and proximity effects. Selecting an optimal frequency necessitates balancing size reduction against efficiency trade-offs.
- 2. Core Material:** Core selection is crucial, requiring materials like Ferrite or Powder Alloys that offer low core losses and stable permeability at elevated frequencies, enhancing efficiency and minimizing thermal rise.
- 3. Winding Layout:** Precise winding configuration significantly impacts both magnetic performance and thermal dissipation. Optimal layouts reduce AC resistance, minimize eddy current losses, and enhance thermal conduction pathways.
- 4. Interleaving:** Strategic interleaving of primary and secondary windings reduces leakage inductance, which is vital for maintaining high efficiency, improving transient response, and minimizing voltage overshoot in high-frequency operations.
- 5. Thermal Management:** High-frequency operation intensifies power losses and heat generation. Efficient thermal management strategies, such as utilizing thermally conductive substrates, adequate heat sinking, and optimized airflow paths, are essential.





- 6. Isolation:** Planar transformers often serve high-isolation applications. Designs must rigorously adhere to defined clearance and creepage standards (IEC/UL) to ensure reliable galvanic isolation and electrical safety.
- 7. Component Selection:** Selecting components optimized for high-frequency operation is essential. Devices with minimal parasitic inductance and capacitance, along with robust thermal and power handling capabilities, significantly enhance system reliability and performance.
- 8. PCB Layout:** PCB design critically influences high-frequency power supply performance. Minimizing parasitic inductances, reducing loop areas to limit EMI, and ensuring effective heat dissipation pathways are fundamental to achieving optimal operational efficiency.
- 9. EMI/EMC Considerations:** High-frequency power conversion inherently increases electromagnetic interference. Designs must integrate EMI mitigation techniques (e.g., shielding, filtering, grounding strategies) to achieve compliance with stringent regulatory standards.
- 10. Control Loop Stability:** High-frequency converters demand meticulous control loop compensation to guarantee stability across varying load and input conditions. Designers should implement robust feedback mechanisms and thorough stability analysis.
- 11. Protection Features:** High-current inductors must be properly rated to prevent magnetic saturation under fault conditions. Integrating comprehensive overcurrent, overvoltage, and thermal protection into the power supply ensures system resilience and reliability.
- 12. Regulation and Efficiency:** While high-frequency switching supports compact and efficient switched-mode power supplies, managing losses—particularly switching, conduction, and core losses—is critical. Careful design ensures consistent voltage regulation and maximized overall efficiency. However, efficiency can drop at high frequencies due to increased switching losses, so this needs to be carefully managed.



PARTNER | SOLVE | DELIVER®



**Standex Electronics**

**Worldwide Headquarters**

4150 Thunderbird Lane  
Fairfield, OH 45014 USA  
+1.866.STANDEX (782.6339)  
[info@standexelectronics.com](mailto:info@standexelectronics.com)

Agile Americas (NH)  
+1.800.805.8991  
[info@agilemagco.com](mailto:info@agilemagco.com)

Minntronix Americas (SD)  
+1.605.884.0195  
[productsales@minntronix.com](mailto:productsales@minntronix.com)

Renco Americas (FL)  
+1.800.645.5828  
[sales@rencousa.com](mailto:sales@rencousa.com)

StandexMeder Europe (Germany)  
+49.7733.9253.200  
[salesemea@standexelectronics.com](mailto:salesemea@standexelectronics.com)

StandexMeder Asia (Shanghai)  
+86.21.37606000  
[salesasia@standexelectronics.com](mailto:salesasia@standexelectronics.com)

Standex Electronics India (Chennai)  
+91.98867.57533  
[salesindia@standexelectronics.com](mailto:salesindia@standexelectronics.com)

Standex Electronics Japan (Kofu)  
+81.42.698.0026  
[sej-sales@standex.co.jp](mailto:sej-sales@standex.co.jp)



[standexelectronics.com](http://standexelectronics.com)  
MAG-COM-WP250202 R07/25